

Product data sheet

Vectorpark

Article number: 10163191

General Data

| | |
|---------------------------------|--------------------------------|
| Format | 10.5 x 137 x 0790 mm |
| Wood type | Oak |
| Colour | Avorio |
| Grading | 24, lively |
| Surface treatment | natural oiled |
| Surface structure | brushed |
| Bevel | beveled 4V |
| Filler | dark brown |
| Number of layers | 2 |
| Top layer thickness | 3.5 mm |
| Connection | Tongue + groove |
| Laying pattern | Shipdeck, English, Herringbone |
| Installation method | glued to subfloor |
| Quantity per package | 3.25 m ² /package |
| Gross weight per packaging unit | 19 kg |
| Wood origin | |
| Top layer | Oak, Europe |
| Sublayer | Spruce, Europe |

Technical Data

| | |
|--|--------------------------|
| Release of formaldehyde acc. to EN 14342 ¹⁾ | E1 |
| Grammage | ~5.692 kg/m ² |
| Top layer brinell hardness ²⁾ | ~38 N/mm ² |
| Shrinkage and swelling mass ³⁾ | 0.25 % |
| Underfloor heating (heat transfer resistance) | 100% convenient |
| Moisture content | 5-9 % |
| Fire resistance acc. to EN 14342 and EN 13501-1 | Dfl-s1 |
| Slip resistance grade | |
| acc. to CEN/TS 15676 ⁴⁾ | USRV 60 |
| acc. to DIN-EN 51130 ⁵⁾ | R10 |
| Thermal conductivity acc. to EN 14342 | 0.148 |
| Breaking resistance | NPD |

¹⁾ The lowest emission class E1 according to EN 14342 specifies a value of <124 µg/m³.
Bauwerk Parkett products fulfil these requirements with a very low value of less than 10 µg/m³.

²⁾ At 7 % wood humidity

³⁾ Top layer in open storage, for a 1 % change in wood humidity

⁴⁾ Pendulum test

⁵⁾ Inclined surface







Product data sheet

Vectorpark

Article number: 10163191

Certificates

| | |
|---------------------------|---|
| ecobau | «base», does not infringe criteria of exclusion of Minergie-ECO |
| eco-INSTITUT label | fulfilled |
| French VOC label | A+ |
| FloorScore® certification | fulfilled |
| Wood label | Wood from controlled sources |

| | |
|---|--|
|  | ecobau The independent ecobau association in Switzerland tests and assesses construction products in terms of their environmental impact across their entire service life. The essential components of this testing include the grey energy involved in the manufacture and disposal, as well as the components and emissions arising during use. Many of our parquets, as well as adhesive and accessory products have been tested for compliance with Minergie Eco structure and ecoDevis requirements. |
|  | eco-INSTITUT The Eco-Institut Label is recognised as an international quality seal for low-pollutant, low-emission products by e.g. the building assessment programmes LEED, BREEAM and DGNB. The certified Bauwerk Parkett products were tested by the Eco-Institut for any emissions or substances that may be harmful to health, fulfil the strict requirements and help to reduce the level of harmful substances within your own four walls. |
|  | Émissions (VOC) A French regulation adopted in 2011 requires certain construction products to be marked with an emission class. The emission testing assesses 10 individual substances and the TVOC value. |
|  | FloorScore® FloorScore® is the most recognised certification standard for the quality of ambient air used with hard floor materials, adhesives, and sub-flooring products in the United States. It was developed by SCS in conjunction with the Resilient Floor Covering Institute (RFCI), a leading industry association of floor manufacturers and suppliers, and it qualifies for many green construction programmes, such as LEED v4.1, WELL, BREEAM, CHPS, and Green Globes. |
|  | FSC® FSC® (Forest Stewardship Council®) was founded to promote green, socially beneficial, and commercially viable management of the world's forests. It is an international certification system for sustainable forestry management. The timber used in FSC®-certified Bauwerk Parkett products comes from forests managed in a responsible manner. The global FSC® standards for forestry and production chains complement the label of origin and set supervision and management regulations, and unlike local laws, are inspected by independent bodies every year. All products by Bauwerk Parkett marked 'FSC® 100 %' or 'FSC Mix 70 %' are always delivered with an FSC® certificate. All other 2-layer products (except for those of North American wood types) can be ordered with proof of FSC® compliance as a special option. Proof of FSC® compliance will not be provided after delivery. Good to know: If an FSC® certificate is required for a project, we can use products that are FSC® 100 % as well as FSC® Mix 70 %. |
|  | EPD* The Environmental Product Declaration (EPD) is a certified document that provides comprehensive information about the environmental impact of a construction product. EPD plays a critical role, as it enables a transparent look into the environmental footprint of the product. It provides information about the consumption of energy, CO2 emissions, and other environmental values applicable across the entire life cycle of the product. With EPD, buyers can make sustainable decisions, preferring products with lower environmental effects, and contributing to the promotion of eco-friendly practices in construction. |

* General information